

## The effects of rain fade on millimetre wave channel in tropical climate

Asma Ali Budalal<sup>1</sup>, Islam Md Rafiqul<sup>2</sup>, Mohamed Hadi Habaebi<sup>3</sup>, Tharek Abd. Rahman<sup>4</sup>

<sup>1,2,3</sup>Departmental of Electrical and Computer Engineering,

International Islamic University of Malaysia, 53100 Kuala Lumpur, Malaysia

<sup>4</sup>Wireless Communication Center, Universiti Teknologi Malaysia, Kuala Lumpur 54100, Malaysia

---

### Article Info

#### Article history:

Received Jan 9, 2019

Revised Feb 24, 2019

Accepted Mar 17, 2019

---

#### Keywords:

38 GHz propagation

measurement

5G system

Channel model

Millimeter-wave

Rain attenuation

---

### ABSTRACT

The main objective of this paper to determine multipath and time-varying channel behaviour of short-terrestrial millimetre-wave point-to-point radio links. In an attempt to invigorate the impact of rain attenuation on mm-wave channel parameters such as the RMS delay spread, path loss received power strength and Rician distribution with a K factor. A brief analysis of rain fading was presented based on the simultaneous measurement of one-minute rain rate and its effects on a short experimental link of 38 GHz. Rain fade average is observed as high as 16 dB for 300 m path at about 125 mm/hr rain intensity. The statistical spatial channel mode (SSCM) simulation software was utilized for an operating frequency of 38 GHz. To generate of power delay profile (PDP). For both omnidirectional and directional antenna. The RMS delay spread and path loss has been estimated using the environmental parameters of Kuala Lumpur city which illustrates the theoretical performances of 5G in Malaysia. It is observed that RMS delay spread, path loss received power strength and K factor effected dramatically by rain fade. (SSCM) simulation software has to be modified to consider rain fade dynamic characteristics to achieve ultra-reliability requirements of outdoor applications in the tropical regions. This study is important for understanding signal propagation phenomena in short distance and enabling the utilization of the millimetre wave band for an urban micro-cellular environment for 5G communication system.

*Copyright © 2019 Institute of Advanced Engineering and Science.*

*All rights reserved.*

---

### Corresponding Author:

Islam Md Rafiqul,

Department of Electrical and Computer Engineering,

Faculty of Engineering, International Islamic University Malaysia,

53100 Kuala Lumpur, Malaysia.

Email: rafiq@iium.edu.my

---

## 1. INTRODUCTION

Millimetre wave communication for wideband systems revolutionized the way we live in today's world. It solves the problem of the limited bandwidth with high demand greater data rate for mobile devices [1]. Millimetre wave considered as the extremely high frequency (EHF) with wavelengths ranging from 1 to 100 mm [2]. It has fundamental access to 10 Gbit/s bandwidth with the highest data rates [3]. Hence it is highly recommended for future applications and service such as real-time video streaming and the rise of the Internet-of-Things [4]. It can be utilized to provide high throughput in a small geographic area.

To handling this request, the wireless communication is moving to its (5G) cellular innovation with huge amounts of connected devices. 5G systems have promised an ultra-low latency between 1 ms to 10 ms which offers rise to the best performance [5]. Due to the extremely small wavelength at mm-wave frequencies makes it possible to pack many high gain antennas array on-chip into the mm-wave transceivers. CMOS technology can now operate well into the millimetre wave spectrum in a Cost-effective manner [6].

Millimeter Wave communication systems can employ highly directional antenna using beamforming gain to improve spectral efficiency and reduce the impact of interference [6]. They are characterized by inherent security and privacy because of narrow beam width and limited range. Samsung stated it is 5G system effectively achieving 1Gbps in the 28 GHz band, contrasted with 75 Mbps achieved by (4G LTE) [7]. However, some challenges faced by wideband communications become clear and must be solved [6], [8], [9]. Since each country has different climate parameters, it requires a channel model of 5G developed independently to accomplish the best performances.

Malaysia, characterized by heavy and high rain rates such as a monsoon at a rate of 150mm/h with large raindrop sizes. The raindrop size distribution changes according to geographical location, and they can approach the size of radio mm-waves. Hence, due to their comparable sizes, mm-Wave signals are more exposed to blockage by raindrops than signals with longer wavelengths [2]. The mm-wave signals can be absorbed, scattered, depolarized, and diffracted by rain. This can restrict their propagation, causing high signal attenuation loss through effective propagation path length [2], [10]. The level of rain attenuation increases when the rain rate, operating frequency, rain density, or effective length are increased. If the air is not clean, the rain attenuation and atmospheric absorption increase the path loss and limit the communication range [11, 12]. As such, high rain attenuation of the mm-wave band in tropical regions stand out as a key obstacle facing the implementation of the 5G wireless system.

In millimetre wave networks, a received signal level and interference dynamically vary due to rain attenuation. These physical layer variations have an influence on upper communication layers. Which yields to variable network capabilities to serve traffic demands. Since the designer of 5G communication system looking for 99.999% availability. The rapid channel variation reduces the reliability, availability, and performance of the millimetre wave links [13]. Thus, this paper will examine the impact of rain fade on the millimetre wave channel characteristic parameters such as received power strength, power delay profile and, RMS delay and, coherence bandwidth, and coherence distance. In order to clarify facilitate implementing mm-wave communications for a typical 5G cell size in the tropical region.

Having a good knowledge of the propagation channel characteristics over mm-wave frequencies is considered as a major subject to conduct accurate and reliable 5G communication systems within small cell design. This paper presents wide-band (800-MHz RF bandwidth) propagation under rain conditions at millimetre-wave frequencies over short terrestrial links region tropical in small outdoor cell systems. It has also reported on real measurement data of one-minute rain rate and measured receive signal level simultaneously, in 0.3 km experimental link of 38 GHz. A preliminary analysis on Malaysia 5G channels by utilizing statistical spatial channel mode SSCM simulation software, for an operating frequency of 38 GHz have been presented. The rain impact over the propagation path is analyzed for the average value of rain rate from direct measurement input to NYUSIM software simulation. This model developed in the temperate region New York University [14]. This study can be considered as a portrayal preliminary simulation in Malaysia to investigate the performance of 5G channel during the rainy event. The motivation of this primary study is to investigate challenges and future possibilities in mm-wave applications in tropical areas.

## 2. MM WAVE PROPAGATION CHARACTERISTICS

Millimetre wave propagation characteristics should be considered for the reliable design of 5G cellular communications. mm-Wave has a higher path loss hence; the coverage will be restricted [15] which make it most appropriate for use in outdoor small cell scenarios and in indoor hotspots [16]. Shadowing impacts and various attenuation losses such as dry air, vapour, haze, and rain of the mm-Wave channel become more challenging at mm-wave frequencies. Millimetre channel characteristic is illustrated in Figure 1. Interference and mobility become more challenge as well as rapid channel fluctuations and intermittent connectivity. As attenuation and atmospheric absorption increase, the path loss limits the coverage [11]. There is a requirement for new knowledge into design and protocols to overcome some impediment such as path loss, higher penetration, precipitation, directivity, foliage losses, sensitivity to blockage. A number of researchers [7], [17], [18] identified some of the essential difficulties and major propagation issues from utilizing mm-Wave for 5G cellular communications and these include:




Figure 1. mm Wave propagation characteristics [19]

**2.1. Path loss and large-scale fading**

Path loss describes the drop-in effective transmit power of wireless signal through the channel, which is determined as [2]:

$$PL [dB] = 10 \log_{10} \frac{P_T}{P_R} \tag{1}$$

Large-Scale Fading characterizes the average received signal strength over the large T-R propagation distance. Path loss could be because of numerous impacts, such as free-space loss, significant diffraction, refraction, coupling loss, and absorption [20].

$$L(d) = P_t + G_t + G_r - P_r(d) - L_0 [dB] \tag{2}$$

$G_t$  and  $G_r$  indicate TX and RX antenna gains respectively in dBi, and  $P_t$  and  $P_r$  respectively illustrate, transmitted power and received power in dBm, and  $L_0$  is mm-Wave link loss in dB [21].

**2.2. Small-scale fading**

Small-scale fading is used to characterize the fast variance of the average received signal strength and phase over a very short distance or period duration as a consequence will complicate the channel impulse response (CIR). There are different models for calculating path loss developed based on experimental data designed to fit a certain scenario or environment [14] such as:

$$PLCI(f, d) [dB] = FSPL(f, 1 \text{ m}) [dB] + 10n \log_{10}(d) + AT [dB] + \chi\sigma \text{ CI, where } d \geq 1 \text{ m} \tag{3}$$

where the carrier frequency represented as  $f$  in GHz, the distance is  $d$ , and the path loss exponent (PLE) is  $n$ , the attenuation denoted as  $AT$ ,  $\chi\sigma \text{ CI}$  represents a zero-mean Gaussian random variable for standard deviation  $\sigma$  in dB, and the free space path loss is  $FSPL(f, 1 \text{ m})$  in dB at a T-R distance of 1 m.

$$AT [dB] = \alpha [dB/m] \times d [m] \tag{4}$$

Where  $\alpha$  is the scattering coefficient and the attenuation represents as dB/m for frequency ranging from 1 GHz to 100 GHz [14].

**2.3. Blocking**

Millimeter wave links are highly vulnerable to both user and environmental mobility. Since mm-wave radios use directional antennas, different obstacles such as high-rise buildings, furniture and human the block the (LOS) signal. In [4] the complex indoor situation, it is likely that the blocked Millimeter wave communication link cannot be restored no matter how the access point and the mobile user change their antenna directions. Most of the connections at 28 GHz NLOS, being partly and heavily blocked by high rise buildings, foliage, and vehicular activity [14].

#### 2.4. Millimeter wave human blockage

Blockages of millimeter-wave communication attenuation by human greatly affect link performance. A model has been presented to investigate the impact of human blockage at 73 GHz link [22]. The research found that a person could induce more than 40 dB of loss when standing 0.5 m from the TX antenna or the RX antenna, with a signal decay rate of 0.4 dB/ms at walking speeds. Hence, human blockage is a big issue yet to be fully modeled.

#### 2.5. Considerations on spatial consistency

Spatial consistency can impact so many aspects of 5G system evaluations. It should be considered as an essential feature in channel modelling rather than an optional one, in the high-frequency channel modelling study item [23].

#### 2.6. Penetration and other losses

The penetration loss is considering one of the most major challenges in implementing 5G cellular communication at mm-wave frequencies. During the communication, signals penetrate through the walls and this will produce a very high penetration loss and causes system performance degradation. It is found that the penetration loss quality is lower for dry walls and clear glass at 28 GHz link. In contrast, it is high for brick and tinted glass with about 28 dB and 40 dB for 28 GHz signals [24]. The result of an intensive study at 28 GHz indicates that the penetration loss is around 26.5 dB for a concrete wall of 40 cm thickness, while it is higher than 40 dB at 60 GHz signals for the same concrete wall. The previous study mentioned that 28 GHz is more favorable for mobile communications, particularly in Non-Line of Sight (NLOS) environment [25].

Doppler effect in wireless communication leads to change in the received signal frequency due to motion between transmitter and receiver. Fundamentally line-of-sight (LOS) causes degradation of the link performance [19].

#### 2.7. Link budget of 5G signal

Link budget of 5G signal consider all effects of mm-wave propagation which, depending on the frequency and scenarios of interest represented. In the example below: Received power in dBm = Tx power + Tx antenna gain + Rx antenna gain - path loss - rain fade (est. 2dB/200m) - shadowing loss (20 to 30dB) - foliage loss (10 to 50dB) - atmosphere absorption - terrain/humidity - Fresnel blockage - system margin. Fresnel zone radius (R) =  $17.32 \times \sqrt{(d/4f)}$  (d in km, f in GHz). By examining the above equations, it is obvious that many factors can cripple mm-Wave links. The link budget is the most important area of focus for any 5G deployment team.

### 3. RMS DELAY SPREAD

The Root Mean Square (RMS) delay spread ( $\tau_{RMS}$ ) is a parameter that characterizes the propagation delays of a channel. This is an important result that has implications on the data rates that can be transmitted through these channels. RMS is useful in estimating if the channel will cause inter-symbol interference without the use of an equalizer. Generally, given ( $\tau_{RMS}$ ), it is requiring ( $\tau_{RMS}/T_s$ ) symbols to be equalized to remove the inter-symbol interference effect for symbol rate  $1/T_s$ . Thus, it has to consider the root mean square delay spread RMS [26, 27]. It is the most commonly used one for measuring the delay time. BER is dependent on the RMS delay spread as well. The cyclic prefix in OFDM system is typically determined by maximum excess delay or by the RMS delay spread of the environment. The RMS delay spread can be expressed as:

$$\tau_{RMS} = \sqrt{\frac{\int_0^{\infty} (\tau - \tau')^2 p(\tau) d\tau}{\int_0^{\infty} p(\tau) d\tau}} \quad (5)$$

Where is  $p(\tau)$  the power delay profile of the channel,  $\tau'$  is the average delay of the channel.

### 4. THE RICAN K-FACTOR

The distribution of the short-term received signal envelope after propagating different paths can be described by a-Rice distribution [26]. The Rican K-factor specifies the ratio of the strongest multipath power  $P_{max}$  to the sum of powers of the other weaker multipath, as in the equation below:

$$K = \frac{P_{max}}{P_{tot} - P_{max}} \quad (6)$$

Where  $P_{\text{tot}}$  is the total received power from all multipath components (e.g. area under the PDP curve). The K-factors were computed to determine whether strong multipath components exist in LOS and NLOS environments [28, 29]. In LOS environments, this will be the ratio of the power of the first arriving multipath component to the sum of powers of all later arriving multipath components. This was suggested by industry users. There is a strong relationship between the rain rate and k factor:

$$K = 16.88 - 0.04R_{dB} \quad (7)$$

Relationship between the Rician factor (dB) and rain rate (mm/h) as (7). (7) shows that the factor is proportional (with a negative sign) to rain rate [28]. In this paper, the Rician K-factor has been calculated for every PDP and is an output parameter in the data file for each simulation run to investigate the impact of tropical rainfall characteristics in this important parameter in mm-wave channel.

## 5. RAIN-INDUCED FADING

Millimetre-wave transmission can encounter critical attenuation during heavy rain [30]. At 25 mm/h rain rate can introduce attenuation more than 10 dB/km a range of frequencies 60 to 73 GHz. Rain attenuation even reaches up to 30 dB/km if the rain rate reaches 100 mm/h in tropical regions [31]. Recent studies in outdoor urban-microcell (UMi) propagation at millimetre-wave showed that future cell radii of cellular communication will be 200 m [31]. Hence at such short path length, atmospheric and rain attenuations can be ignored [12]. However, most of these measurements were implemented in temperate regions. On the other hand, in different tropical areas with consistent and heavy rainfall, rain attenuation impact cannot be discounted even for this small cell size. It emerges as a key impediment facing the implementation of the next generation of smartphones. Thus, extensive research on channel characterization during rainfall is required to develop an accurate rain fade prediction for a wide range of mm-Wave frequency bands [12]. Rain rate and rain fade based on real measurement data implemented in Malaysia at 38 GHz with 300 m TX to RX separation distance at LOS environment have been reported in order to explore the effects on mm-wave bands in outdoor activities for 5G systems in tropical regions. The specification of the link illustrated in Table 1 and Figure 2.

Table 1. Measured link specification

Frequency Band (GHz)	37.0-39.5 GHz	
Polarization	Horizontal	
Maximum Tx Power dBm	+15.0	
Receive Threshold (dBm)	-79.0	
Tx & Rx Antennas	Gain (dBi) 44.9	Size 0.6 m
Antenna beam width	10°	
Link bath length	300m	




Figure 2. The radio link system configuration based on MINI-Link 38 E unit [31]

The rain rate and received signal strength data were periodically monitored and logged daily for every minute during rainy events, in 24 hours via the data logger for fifteen months from Jan 1999 to Mar 2000. The collected data were analyzed with developing MATLAB software code to obtain the average yearly rain

attenuation and rain rate [1]. Existing rain fade prediction models are based on path reduction factors techniques. This approach used with link typically more than 1.0 km. The path reduction factor is assumed to approximately equal to 1 for shorter link lengths (typically less than 1.0 km) because rain rate would be uniform along the path [32], [33]. ITU-R 530-17 prediction model [32] has been used to compare measured and predicted values of rain fade. Direct original measurement has given an average value of 125 mm/h at 0.01 % of time rain rate exceeded [1].

### 5.1. Rain attenuation measurements at 38 GHz

The equivalent, path attenuation along LOS a 300m link for horizontally polarized was calculated by the difference between the RSL during clear sky conditions and the RSL during rain. That is,

$$\text{Attenuation} = \text{RSL}_{\text{clear sky}} - \text{RSL}_{\text{rainy}} \quad (8)$$

Moreover, the increase of mm-wave signal attenuation due to rain was measured with reverence to free space path loss. In free space, the received signal power  $P_r$  via an unobstructed LOS path with no multipath components is given by:

$$Pr(\text{dBm}) = Pt + GT + GR - 20 \log_{10} \frac{(4 \times \pi \times d)}{\lambda} - PL(\text{rain}) \quad (9)$$

Where  $P_t$  transmitted power;  $G_T$  transmitter gains;  $G_R$  receiver gains  $\lambda$  wavelength;  $L$  path length. (9) and has been used to measure attenuation due to rain as well. Moreover, rainfall rate measurements data  $R$  has been converted into an equivalent value of rain attenuation  $A_R$  along the path of the 300-m link using the power-law approximation:

$$A_R \propto \frac{KR^\alpha}{1000} \times 300 \left( \frac{\text{dB}}{\text{m}} \right) \quad (10)$$

Parameters  $k$  and  $\alpha$  depend on frequency, rain temperature, and polarization; and their values can be obtained from ITU-R P.838-3 [34]. The worst two rainy events, individually, in February have been plotted in Figure 3 with measured rain rate data and measured receive signal level for the same period. The results presented in Figure 3 indicates that received signal strength has been sharply decreased by around 22dB during the heavy rainfall event on 16/02/2000, 6.6 dB/m.




Figure 3. Measured rain rate and the corresponding received signal strength on experimental Mini-links at 38 GHz operating in Malaysia

In Table 2, recorded absolute path loss & rain attenuation values at 38 GHz for horizontal polarization by link, measurement date, and weather condition. Figure 4 and 5 present the differences between signal attenuation on a clear sky and signal attenuation on rainy events. On a clear day, the signal received is above the attenuation threshold, -25.5 dB. This weather, the mm-wave link not recorded any outage due to rain attenuation. But on the rainy weather the signal received at the receiver is below the attenuation threshold, -25.5 dB. This happens due to the interference caused by raindrops and mm-wave signal travelling through the atmosphere. When this phenomenon occurs, the transmission is weakened by scattering more than the absorption of the signal by raindrops. Hence, the number of multipath components will increase. As a result, the 5G systems that operate during this duration will experience an outage due to rain attenuation and difficult to achieve ultra reliability requirements of outdoor applications at tropical regions. Thus, the use of suitable beamforming access techniques will be needed to maintain the ultra-reliable system operation.




Figure 4. Received Signal level time series during rain events




Figure 5. Received Signal level time series during clear-sky

Table 2. Absolute path loss & rain attenuation values at 38 GHz, 23/2/2000 from 17:8 to 17:23pm

LOS Rain Attenuation Measurements at 38 GHz (Horizontal Polarization) and (300 meter LOS Millimeter wave-Link)		
Rain rate mm/h	Path loss in dB	Rain attenuation in dB
30	104.08	6.72
30	105.42	8.06
30	104.90	7.545
30	105.88	8.52
60	107.15	9.79
60	108.63	11.27
60	108.87	11.51
60	110.21	12.85
90	111.55	14.20
120	108.33	10.97
90	112.90	15.54
120	112.18	14.71
120	115.59	18.23
150	114.05	16.68
90	108.17	10.81

The path loss rain rate and rain fade values, shown in Table 2, illustrate a clear trend. At lower rain rates, total path signal attenuation experienced by the propagating millimetre wave is comparatively small. With an increase in rain rate, the dropping level in received signal strength (RSS) increases linearly. It's observed that the received signal fluctuations increase rapidly during rainy events. The path loss exponent is an experimental constant that is often measured, however, can as well be derived theoretically in some environments. From the data measured results, it was 3.28 during rain and proximity 2 at clear sky weather. It differs depending on the millimetre wave signal propagation environment and describes, the rate at which path loss rises with Tx to RX separation distance for a given propagation environment.

**5.2. Comparison with rain models**

In this section, the rain attenuation values, calculated from data files, are compared with rain models described in Section 5.1. For a given short path between the transmitting and receiving antennas, compares the rain attenuation values in Table 2, measured for horizontal polarization configuration, with corresponding values predicted by the ITU-R 530-2017 attenuation model for different rain rates. the measured and predicted attenuation is compared at 0.1 %, 0.01 % and 0.001 of the time, as follows. The average value of measured rain fade is 4.71 dB, 10.84 dB and 16.25 dB, whereas the ITU-R predicted values are 3.8 dB, 8.5 dB and 11.6 dB, respectively. It's clear that ITU-R model underestimates rain attenuation in the tropical climate [35-39]. Thus, more accurate prediction models for short mm-wave terrestrial link are needed. A preliminary analysis of Malaysia 5G channels by utilizing statistical spatial channel mode SSCM simulation software, for an operating frequency of 38 GHz have been presented. The rain impact over the propagation path is analyzed for the average value of rain rate from direct measurement input to NYUSIM software simulation [1]. This model developed in the temperate region of New York University. It's found that NYUSIM main code considers Law and Parsons Rainfall DSD Model.

The Laws and Parsons model has been shown to be more suitable for temperate regions and not an accurate model for rainfall DSD estimation for regions outside Europe and North America. As well as in 3GPP channel model have used ITU-R model. Thus, it considers not accurate to investigate the performance of 5G

channel during the rainy event in the tropical climate. Since the designer of 5G communication system looking for 99.999% availability [1]. According to the above results, it is recommended to propose and develop an efficient prediction model to investigate the worst-case scenarios that will be more accurate for cellular communications services in tropical regions. Rapid channel fluctuations and intermittent connectivity considered one of the key challenges in understanding the implementation of cellular communications in the mm-wave band [3]. It is obvious to say that during the rain event the fluctuation of amplitude and phase on mm-wave signal have been increased. This will impact the dynamic channel impulse response. As well as all small-scale parameters of the channel expected to change at heavy rain events. This physical layer fluctuation produces an impact on upper layers of the communication system, which leads to variable system capacities and instability to serve data rate request [5]. Therefore, in design mm-wave communication systems at 38 GHz, the analysis of the statistical and dynamic behaviour of rain fading must be investigated thoroughly.

### 5.3. Millimeter wave terrestrial link availability

Availability, which refers to the system constancy against possible outage scenarios. It's defined as the probability that a given service is available (i.e., coverage). Which denote the presence or absence of link reliability. Hence, availability reflected the link reliability. It is affected by path loss, shadowing, rain fade, and other large-scale parameters of the channel. Availability of a service is a geographic characteristic, which varies from place to place, and potentially on long time scales, e.g., related to hardware failures [5]. According to the average measured rain fade at 38 GHz around 16 dB, the probability that the attenuation of the channel is wares than 16dB calculated was 0.02455. In Termes of rain fade, the availability of millimetre-wave link depends on the probability of occurrence of heavy rain to cause an outage. The percentage availability of mm-wave link is tied to the rainfall characteristic of the location where the link is deployed, as well as the path length. In this case, the availability can be presented as:

$$\text{Availability} = 100\% - \text{outage} \quad (11)$$

## 6. ANALYSIS IN MALAYSIAN TROPICAL CLIMATE STATISTICAL CHANNEL MODELS

In this paper, we considered Kuala Lumpur city climate parameters, which is in the tropical region with high rain rate, large raindrop sizes and strong thunderstorms over the year. Considering a bandwidth of 800 MHz with a carrier frequency of 38 GHz for 5G in outdoor, we investigate the performance of the channel in an urban microcell (UMi). The signal propagation, both LOS were conditioned at 300m T-R separation distance. The directional and omnidirectional receiver (RX) antennas were utilized [1]. The average value of rain rate, humidity, temperature, and barometric pressure as climate parameters obtained from real measurements are shown in Table 3 as input to NYUSIM software simulation [14]. Where delay profile PDP was generated to estimate the number of multipath components above the noise threshold, the power of the LOS component, the absolute propagation time, path loss due to atmospheric attenuation and multipath scattering, path loss exponent and RMS delay spread. Statistical results are outlined in the next sections.

Table 3. Input channel parameter to the NYUSIM of Kuala Lumpur City represent of 5G Malaysia

Input Channel Parameters	Value(s)
Frequency	38 GHz
Channel bandwidth	800 MHz
Condition	UMi
Environment	LOS
TX-RX separation distance	300m
TX Power	15 dBm
Barometric Air Pressure	1010.00 mbar
Humidity	85%
Average Temperature	28°C
Average Rain Rate	125mm/hr
Foliage Loss	0.4dB

Generated PDP's are classified by links Tx to Rx separation distance, and weather condition summarized in Table 3. A comparison of the PDP's under various weather conditions is given in Figures 6, 7, 8, 9. Xu et al showed that multipath could occur at the edges of very intense and compact rain cells. Pressure, temperature, and rain could change the refractivity of the atmosphere, thus creating fluctuating propagation paths and propagation delays. It's observed that rms delay was higher in case of omnidirectional transmission, while it was lower at the directional antenna. Results show that, with considering rain, the RMS delay spread can be as high as 21.9 ns on the omnidirectional antenna LOS path, and 6.5 ns on the directional antenna. The



difference in rms delay was 4ns and 3.6 ns between clear sky and rain in omnidirectional and directional antenna respectively. The scattered power and the delay spread are larger for omnidirectional antennas. It's worthy to mention that directional antennas boost the received power and coherence bandwidth (BC). This is because when directional antennas are used, most of the reflectors and scatterers will fall outside the antennas beam width [3]. It is inversely proportional with  $\tau_{RMS}$  [Bc  $\propto 1/\tau_{RMS}$ ] BC parameter represents delay spread in the frequency domain, which quantizes the frequency differences of the wireless channel.

The minimum received power of each multipath component) determined by the transmit power, dynamic range (DR) of simulation system (190 dB) and a 10 dB SNR, dynamic range maximum possible omnidirectional path loss in dB, according to T-R separation distance. If T-R separation distance is no larger than 500 m, then set dynamic range as 180 dB, otherwise set it to 220 dB threshold  $Th$  equals the transmit power in logarithmic scale minus 180 dB [14].

$$Th = TX \text{ Power} - DR \tag{12}$$

The Ricean K-factor has been calculated for every PDP and is an output parameter in the data file for each simulation run. It was -5.568 in case of rain condition while it recorded -2.076 at clear sky weather. Ricean K-factor decreases with increasing rain rate due to increase power of the reflected multipath components [26]. The result showed a decrease in the LOS power as the multipath power increases during rain. (7), combined with the received total power estimate, provides a powerful tool to model received signal variation and the resultant outage probability for mm-wave systems

Data files created from NYUSIM can be utilized to simulate CIRs for mm-Wave systems. The omnidirectional path loss is found lower than directional path loss in scenarios LOS .It was close to measured values than directional antenna scenario. However real measurement of shadow fading and path loss exponent are also needed. It is found that received power decreased by 6.4 dB in Malaysia link compared with a link at temperate region because of path loss was higher at 38 GHz when taking rain fade into consideration. It is observed that the path loss difference because of other weather parameters (humidity, temperature, and barometric pressure) only influence the link by increasing path loss by 0.1 dB.




Figure 6. Directional LOS-PDP with at clear sky




Figure 7. Directional LOS-PDP R=125 mm/h




Figure 8. Omnidirectional LOS-PDP at R=0 mm/h




Figure 9. Omnidirectional LOS-PDP at R=125 mm/h

## 7. CONCLUSION

Millimetre wave communication provides high capacity and data speed. In this paper, an overview of the challenges faced by mm-wave that support wideband communications is provided. Major propagation issues from utilizing mm-Wave for 5G cellular communications include path loss, penetration loss, rain fade, blockage, doppler, and multipath. Human blockage is found a big issue yet to be fully understood and modelled. Furthermore, spatial consistency also remains to be investigated and modelled. The main limits of the existing channel models are lack of measurements on bandwidth, spatial characteristics for dual mobility, directional antennas and large-scale antennas for massive MIMO. The main purpose of this paper was to study the impacts of various weather events such as rain on the behaviour of the broadband millimetre-wave channel in tropical area. Averaged attenuation in a Malaysia was measured to be 16 dB over the 300 m path. These allow the designer to define the additional fade margin needed for ultra-reliable operation of broadband communication systems at millimetre-wave frequencies. The preliminary result of Malaysian 5G channels by utilizing statistical spatial channel mode SSCM simulation software for an operating frequency of 38 GHz have been presented. The average value of rain rate, humidity, temperature, and barometric pressure as climate parameters obtained from real measurements in Kuala Lumpur are used as input to NYUSIM software simulation. Multipath statistics shows that while very few multipath components were detected in clear, dry weather, more multipath components were detected during rain. that cussed variation in small scale channel parameters such as RMS delay spread, path loss, path loss exponent and k factor. It is also found that received power decreased by 6.4 dB on the link in Malaysia compared with a link at temperate region because of path loss was higher at 38 GHz when taking rain fade into consideration. It is observed that RMS delay spread effected dramatically by rain fade. This study shows that further investigation is required to model 5G channels in tropical areas.

## AKNOWLEDGEMENT

Authors are grateful to Research Management Center (RMC) at International Islamic University Malaysia (IIUM) to support this research.

## REFERENCES

- [1] A. A. Budalal, M. R. Islam, M. H. Habaebi and T. A. Rahman, "Millimeter Wave Channel Modeling—Present Development and Challenges in Tropical Areas," *2018 7th International Conference on Computer and Communication Engineering (ICCCCE)*, Kuala Lumpur, 2018, pp. 23-28.
- [2] H. Y. Lam, L. Luini, J. Din, M. J. Alhilali, S. L. Jong and F. Cuervo, "Impact of rain attenuation on 5G millimeter wave communication systems in equatorial Malaysia investigated through disdrometer data," *2017 11th European Conference on Antennas and Propagation (EUCAP)*, Paris, 2017, pp. 1793-1797.
- [3] S. Sun, T. S. Rappaport, M. Shafi, P. Tang, J. Zhang and P. J. Smith, "Propagation Models and Performance Evaluation for 5G Millimeter-Wave Bands," in *IEEE Transactions on Vehicular Technology*, vol. 67, no. 9, pp. 8422-8439, Sept. 2018.
- [4] T. S. Rappaport, Y. Xing, G. R. MacCartney, A. F. Molisch, E. Mellios and J. Zhang, "Overview of Millimeter Wave Communications for Fifth-Generation (5G) Wireless Networks—With a Focus on Propagation Models," in *IEEE Transactions on Antennas and Propagation*, vol. 65, no. 12, pp. 6213-6230, Dec. 2017.
- [5] Bennis M, Debbah M, Poor HV. "Ultra-reliable and low-latency wireless communication: Tail, risk and scale". arXiv preprint arXiv:1801.01270. 2018 Jan 4
- [6] Rappaport TS, Sun S, Mayzus R, Zhao H, Azar Y, Wang K, Wong GN, Schulz JK, Samimi M, Gutierrez Jr F. "Millimeter wave mobile communications for 5G cellular: It will work!". *IEEE access*. 2013 May 10;1(1):335-49.
- [7] Zhang J, Tang P, Tian L, Hu Z, Wang T, Wang H. "6–100 GHz research progress and challenges from a channel perspective for fifth generation (5G) and future wireless communication". *Science China Information Sciences*. 2017 Aug 1;60(8):080301.
- [8] L. Wei, R. Q. Hu, Y. Qian and G. Wu, "Key elements to enable millimeter wave communications for 5G wireless systems," in *IEEE Wireless Communications*, vol. 21, no. 6, pp. 136-143, December 2014.
- [9] S. Rangan, T. S. Rappaport and E. Erkip, "Millimeter-Wave Cellular Wireless Networks: Potentials and Challenges," in *Proceedings of the IEEE*, vol. 102, no. 3, pp. 366-385, March 2014.
- [10] Nandi D, Maitra A. "Study of rain attenuation effects for 5G Mm-wave cellular communication in tropical location". *IET Microwaves, Antennas & Propagation*. 2018 Mar 8.
- [11] C. Kourgiorgas, S. Sagkriotis and A. D. Panagopoulos, "Coverage and outage capacity evaluation in 5G millimeter wave cellular systems: impact of rain attenuation," *2015 9th European Conference on Antennas and Propagation (EuCAP)*, Lisbon, 2015, pp. 1-5.
- [12] Y. Zhang, P. Wang and A. Goldsmith, "Rainfall Effect on the Performance of Millimeter-Wave MIMO Systems," in *IEEE Transactions on Wireless Communications*, vol. 14, no. 9, pp. 4857-4866, Sept. 2015.

- [13] M. V. Perić, D. B. Perić, B. M. Todorović and M. V. Popović, "Dynamic Rain Attenuation Model for Millimeter Wave Network Analysis," in *IEEE Transactions on Wireless Communications*, vol. 16, no. 1, pp. 441-450, Jan. 2017.
- [14] S. Sun, G. R. MacCartney and T. S. Rappaport, "A novel millimeter-wave channel simulator and applications for 5G wireless communications," *2017 IEEE International Conference on Communications (ICC)*, Paris, 2017, pp. 1-7.
- [15] T. Bai, A. Alkhateeb and R. W. Heath, "Coverage and capacity of millimeter-wave cellular networks," in *IEEE Communications Magazine*, vol. 52, no. 9, pp. 70-77, September 2014.
- [16] Morgado A, Huq KM, Mumtaz S, Rodriguez J. "A survey of 5G technologies: regulatory, standardization and industrial perspectives". *Digital Communications and Networks*. 2018 Apr 1;4(2):87-97.
- [17] J. Karjalainen, M. Nekovee, H. Benn, W. Kim, J. Park and H. Sungsoo, "Challenges and opportunities of mm-wave communication in 5G networks," *2014 9th International Conference on Cognitive Radio Oriented Wireless Networks and Communications (CROWNCOM)*, Oulu, 2014, pp. 372-376.
- [18] J. G. Andrews *et al.*, "What Will 5G Be?," in *IEEE Journal on Selected Areas in Communications*, vol. 32, no. 6, pp. 1065-1082, June 2014.
- [19] I. A. Hemadeh, K. Satyanarayana, M. El-Hajjar and L. Hanzo, "Millimeter-Wave Communications: Physical Channel Models, Design Considerations, Antenna Constructions, and Link-Budget," in *IEEE Communications Surveys & Tutorials*, vol. 20, no. 2, pp. 870-913, Secondquarter 2018.
- [20] R. W. Heath, N. González-Prelcic, S. Rangan, W. Roh and A. M. Sayeed, "An Overview of Signal Processing Techniques for Millimeter Wave MIMO Systems," in *IEEE Journal of Selected Topics in Signal Processing*, vol. 10, no. 3, pp. 436-453, April 2016.
- [21] Akpaida VO, Anyasi FI, Uzairue SI, Idim AI. "Determination of an outdoor path loss model and signal penetration level in some selected modern residential and office apartments in Ogbomosho, Oyo State, Nigeria". *Journal of Engineering Research and Reports*. 2018 May 25;1(2):1-25.
- [22] S. Nie, G. R. MacCartney, S. Sun and T. S. Rappaport, "28 GHz and 73 GHz signal outage study for millimeter wave cellular and backhaul communications," *2014 IEEE International Conference on Communications (ICC)*, Sydney, NSW, 2014, pp. 4856-4861.
- [23] M. U. Sheikh, R. Biswas and J. Lempiainen, "Performance Evaluation of Coordinated Multipoint Transmission at 28 GHz Frequency Using 3D Ray Tracing," *2018 IEEE 87th Vehicular Technology Conference (VTC Spring)*, Porto, 2018, pp. 1-6.
- [24] Yang Y, Xu J, Shi G, Wang CX. 5G Hardware Test Evaluation Platform. In *5G Wireless Systems*. Springer, Cham. 2018: 301-357.
- [25] G. Noh, J. Kim, H. S. Chung, B. Hui, Y. Choi and I. Kim, "mmWave-Based Mobile Backhaul Transceiver for High Speed Train Communication Systems," *2017 IEEE Globecom Workshops (GC Wkshps)*, Singapore, 2017, pp. 1-5.
- [26] Hao Xu, T. S. Rappaport, R. J. Boyle and J. H. Schaffner, "Measurements and models for 38-GHz point-to-multipoint radiowave propagation," in *IEEE Journal on Selected Areas in Communications*, vol. 18, no. 3, pp. 310-321, March 2000.
- [27] M. K. Samimi and T. S. Rappaport, "Local multipath model parameters for generating 5G millimeter-wave 3GPP-like channel impulse response," *2016 10th European Conference on Antennas and Propagation (EuCAP)*, Davos, 2016, pp. 1-5.
- [28] G. R. MacCartney, S. Deng, S. Sun and T. S. Rappaport, "Millimeter-Wave Human Blockage at 73 GHz with a Simple Double Knife-Edge Diffraction Model and Extension for Directional Antennas," *2016 IEEE 84th Vehicular Technology Conference (VTC-Fall)*, Montreal, QC, 2016, pp. 1-6.
- [29] P. Wang, Y. Li, L. Song and B. Vucetic, "Multi-gigabit millimeter wave wireless communications for 5G: from fixed access to cellular networks," in *IEEE Communications Magazine*, vol. 53, no. 1, pp. 168-178, January 2015.
- [30] Al-Samman, A. M., Rahman, T. A., Azmi, M. H., & Hindia, M. N. (2016). Large-scale path loss models and time dispersion in an outdoor line-of-sight environment for 5G wireless communications. *AEU-International Journal of Electronics and Communications*, 70(11), 1515-1521.
- [31] Shayea I, Abd. Rahman T, Hadri Azmi M, Arsad A. "Rain attenuation of millimetre wave above 10 GHz for terrestrial links in tropical regions". *Transactions on Emerging Telecommunications Technologies*. 2018 Aug;29(8):e3450.
- [32] Propagation data and prediction methods required for the design of terrestrial line of sight systems", Recommendation ITU-R P. 530-17 (12/2017),
- [33] Abdulrahman AY, Rahman TA, Olufeagba BJ, Islam MR. "Using full rainfall rate distribution for rain attenuation predictions over terrestrial microwave links in Malaysia". *Signal Process. Res.*. 2013 Mar 1;2(1):25-8.
- [34] Specific attenuation model for rain for use in prediction methods," ITU-R Rec. P.838-3, 2005
- [35] M.R. Islam, M.M. Alam, A.K. Lwas, S.Y. Mohamad, "Rain Rate Distributions for Microwave Link Design Based on Long Term Measurement in Malaysia," *Indonesian Journal of Electrical Engineering and Computer Science (IJECS)*, 2018; 10(3): 1023-1029.
- [36] Islam Rafiqul Md, Abdulrahman YA, Rahman TA, "An Improved ITU-R rain attenuation prediction model over terrestrial microwave links in tropical region", *EURASIP Journal on Wireless Communications and Networking, Springer Open Journal*, 2012:189 (7 June 2012).
- [37] I. Shayea, T. Abd. Rahman, M. Hadri Azmi and M. R. Islam, "Real Measurement Study for Rain Rate and Rain Attenuation Conducted Over 26 GHz Microwave 5G Link System in Malaysia," in *IEEE Access*, vol. 6, pp. 19044-19064, April 23, 2018.

- [38] M. R. Islam and A. R. Tharek, "Propagation study of microwave signals based on rain attenuation data at 26 GHz and 38 GHz measured in Malaysia," *1999 Asia Pacific Microwave Conference. APMC'99. Microwaves Enter the 21st Century. Conference Proceedings (Cat. No.99TH8473)*, Singapore, 1999, pp. 602-605 vol.3.
- [39] H. Dao, M. R. Islam and K. A. S. Al-Khateeb, "Rain Fade Slope Model in Satellite Path Based on Data Measured in Heavy Rain Zone," in *IEEE Antennas and Wireless Propagation Letters*, vol. 12, pp. 50-53, January 2013.

## BIOGRAPHIES OF AUTHORS



Asma Ali Hussein Budalal received the B.Sc. degree in electrical and electronics engineering from the Faculty of Engineering, University of Benghazi, Libya, in 1999, and the M.Sc. degree in Electrical and Computer Engineering (telecommunications) from international Islamic University Malaysia. From 2000 to 2013, she was an Engineer with technical College of Electrical and Electronics Technology, Benghazi. 2012-2013 she was communication engineering lab coordinator. She is currently pursuing the Ph.D. degree in telecommunications from the International Islamic University Malaysia. Her current research interests include RF propagation, Millimeter-wave communication and channel modelling.



Md Rafiqul Islam (M'02) received his Bachelor of Science in Electrical and Electronic Engineering from Bangladesh University of Engineering & Technology (BUET), Dhaka in 1987. He received his MSc and PhD both in Electrical Engineering from University of Technology Malaysia in 1996 and 2000 respectively. He is currently working as a professor in the Department of Electrical and Computer Engineering, Faculty of Engineering, International Islamic University Malaysia. He has supervised more than 50 PhD and MSc students and has published more than 200 research papers in international journals and conferences. His areas of research interest are wireless channel modeling, radio link design, RF propagation measurement and modeling in tropical and desert, RF design, smart antennas and array antennas design, FSO propagation and modeling etc. He is a Life Fellow of Institute of Engineers Bangladesh and member of IEEE and IET.



Mohamed H. Habaebi (M'99-SM'16) received his first degree from the Civil Aviation and Meteorology High Institute (CAHI), Libya ('91), his MSc in Electrical Engineering from Universiti Teknologi Malaysia ('94), and his Ph.D. in Computer and Communication System Engineering from Universiti Putra Malaysia ('01). He is currently an Associate Professor and the Post Graduate Academic Advisor at the Department of Electrical and Computer Engineering, International Islamic University Malaysia. He heads the research works on Internet of Things at the department. He has supervised many Ph.D. and M.Sc. students, published more 120 articles and papers and sits on editorial board of many international journals. He is actively publishing in M2M communication protocols, wireless sensor and actuator networks, cognitive radio, small antenna system & radio propagation and wireless communications & network performance evaluation. He is an active member of IEEE and an active reviewer to many international journals.



Prof. Dr. Tharek A. Rahman currently is a professor in wireless communication at faculty of electrical engineering, Universiti Teknologi Malaysia. He obtained his BSc (Hons) (Electrical Engineering) from University of Strathclyde, UK, Msc in Communication Engineering from UMIST, Manchester, UK and PhD in Mobile Communication from University of Bristol, UK. He is the Director of Wireless Communication Centre (WCC), Faculty of Electrical Engineering, Universiti Teknologi Malaysia and currently conducting research related to mobile communications, antenna and propagation. He has also conducted various short courses related to mobile and satellite communication to the telecommunication industry and government agencies since 1988. Prof. Tharek has published more than 300 scientific papers in journals and conferences and obtained many national and international awards. He is also a consultant for many communication companies and an active member in several research academic entities.